TURCE DeviceNet™ Physical Media Connectivity

DeviceNet™, (7/8-16UN) minifast® Male Receptacles

- Provides Quick Connection to Field Devices or Enclosures
- Available for 1/2-14NPT, 1/2-14NPSM, 3/4-14NPT and M20 Threads



Housing Style	Female Part Number	Male Part Number	Features	Pinouts
RKF 57 .394 [10.0]	RKF 57-*M	RSF 57-*M	Nickel plated CuZn or stainless steel, 300 V, 9 A, -40° to +105°C, 1/2-14NPSM threads	Female 2 3 4 1. GY 2. RD
RKF 57/NPT .499 [12.7] .7/8-16UN RSF 57/NPT 1.148 [29.2] .998 [25.1] 7/8-16UN 01.142 [29.0] 01.142 [29.0] 01.142 [29.0] 01.142 [29.0]	RKF 57-*M/NPT	RSF 57-*M/NPT	Nickel plated CuZn or stainless steel, 300 V, 9 A, -40° to +105°C, 1/2-14NPT modified length threads	2. RD 3. BK 4. WH 5. BU Male

^{*} Length in meters.

Standard cable length is 0.5 meters. Consult factory for other lengths. Standard housing material is nickel plated brass. "RKF ..."; "RKFV ..." indicates 316 stainless steel housing. For locknuts to be included, add "W/LN" to the end of the part number.