



L _(mm)	Stroke with PS0x-23(S)x80	Stroke with PS0x-23x160	Standard HP	Art.-No
	SS(ES) _(mm)	SS(ES) _(mm)		
130	0(60)	-	PL01-12x130!90-HP	0150-2209
150	20(80)	-	PL01-12x150!110-HP	0150-2281
170	40(100)	-	PL01-12x170!130-HP	0150-1529
200	70(130)	10*(130)	PL01-12x200!160-HP	0150-1518
230	100(160)	20(160)	PL01-12x230!190-HP	0150-1519
270	140(200)	60(200)	PL01-12x270!230-HP	0150-1520
290	160(220)	80(220)	PL01-12x290!250-HP	0150-1521
350	220(280)	140(280)	PL01-12x350!310-HP	0150-1522
420	290(350)	210(350)	PL01-12x420!380-HP	0150-1523
480	350(410)	270(410)	PL01-12x480!440-HP	0150-1524
580	450(510)	370(510)	PL01-12x580!540-HP	0150-1525
760	630(690)	550(690)	PL01-12x760!720-HP	0150-1526
850	720(780)	640(690)	PL01-12x850!810-HP	0150-1527

Allgemeintoleranzen ISO 2768-m

PL01-12x...-HP			Material:	
			Ersatz für:	
Slider-HP			Status:	21.04.2016/dm
			Änderungen	
Gezeichnet:	05.04.2016	D.Marinkovic		
Dateiname:	0186-0409_160421_CAD_PL01-12x...-HP			
NTI AG, LinMot		Masstab	2:1	
		Zeichnungsnummer		Format
		0186-0409		A3

* - reduzierte Force