

Price* : 601.00 GBP



Main

Range of product	Modicon TSX Micro automation platform
Product or component type	Analogue I/O module
Number of channels	4 input module 2 output module
Analogue input type	0...10 V 4...20 mA 0...20 mA +/- 10 V
Analogue output type	0...10 V 4...20 mA +/- 10 V 0...20 mA

Complementary

Analog/Digital conversion	11 bits 0...10 V 0...10 V 11 bits 0...20 mA or 4...20 mA 0...20 mA or 4...20 mA 11 bits + sign +/- 10 V +/- 10 V
Measurement resolution	0...20 mA or 4...20 mA 0...10 V or +/- 10 V
Acquisition period	16 ms 0...20 mA or 4...20 mA 16 ms 0...10 V or +/- 10 V
Response time	400 μ s +/- 10 V or 0...10 V 400 μ s 0...20 mA or 4...20 mA 400 μ s +/- 10 V
Output load	\leq 0.6 Ohm 0...20 mA or 4...20 mA \geq 2 Ohm +/- 10 V or 0...10 V
Protection type	Short-circuit +/- 10 V or 0...10 V Short-circuit 0...20 mA or 4...20 mA
Temperature drift	0.107 %/10 °C 0...20 mA or 4...20 mA 0.054 %/10 °C 0...20 mA or 4...20 mA 0.083 %/10 °C +/- 10 V or 0...10 V 0.068 %/10 °C 0...10 V or +/- 10 V
Input impedance	250 Ohm 0...20 mA or 4...20 mA 2.2 Ohm 0...10 V or +/- 10 V
Current consumption	180 mA
Isolation voltage	1000 V AC
Product weight	0.24 kg

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0908 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
------------------------	---

Contractual warranty

Warranty period	18 months
-----------------	-----------

Wiring Diagram

