

Product datasheet

Specifications



EasyPact TVS differential thermal overload relay 30...40 A - class 10A

LRE355

Main

Range	Easy TeSys
Range Of Product	Easy TeSys Protect
Product Or Component Type	Differential thermal overload relay
Device Short Name	LRE
Relay Application	Motor protection
Phase Failure Sensitivity	Tripping current 130 % of I _r on two phase, the last one at 0 conforming to IEC 60947-4-1

Complementary

Product Compatibility	LC1E40...95
Network Type	AC
Network Frequency	50...60 Hz
Mounting Support	Under contactor Plate, with specific accessories Rail, with specific accessories
Thermal Overload Class	Class 10A conforming to IEC 60947-4-1
Signalling Function	Relay trip indicator
Thermal Protection Adjustment Range	30...40 A
Tripping Threshold	1.14 +/- 0.06 I _r conforming to IEC 60947-4-1
Mechanical Robustness	Shocks: 6 Gn for 11 ms conforming to IEC 60068-2-7 Vibrations: 3 GN conforming to IEC 60068-2-6
Auxiliary Contact Composition	1 NO + 1 NC
[I _{th}] Conventional Free Air Thermal Current	5 A for signalling circuit
[U _e] Rated Operational Voltage	<= 690 V AC
Associated Fuse Rating	40 A aM for power circuit 100 A gG for power circuit 5 A gG for signalling circuit
[U _i] Rated Insulation Voltage	690 V conforming to IEC 60947-4-1
[U _{imp}] Rated Impulse Withstand Voltage	6 kV
Local Signalling	Trip indicator
Control Type	Push-button red stop: Push-button green reset:
Temperature Compensation	-20...60 °C

Connections - Terminals	<p>Signalling circuit: screw clamp terminals 2 1...2.5 mm² - cable stiffness: flexible without cable end</p> <p>Signalling circuit: screw clamp terminals 2 1...2.5 mm² - cable stiffness: flexible with cable end</p> <p>Signalling circuit: screw clamp terminals 2 1...2.5 mm² - cable stiffness: solid without cable end</p> <p>Power circuit: screw clamp terminals 1 4...35 mm² - cable stiffness: flexible without cable end</p> <p>Power circuit: screw clamp terminals 1 4...35 mm² - cable stiffness: flexible with cable end</p> <p>Power circuit: screw clamp terminals 1 4...35 mm² - cable stiffness: solid without cable end</p>
Recommended Tightening Torque	<p>Power circuit: 9 N.m - on screw clamp terminals</p> <p>Signalling circuit: 1.7 N.m - on screw clamp terminals</p>
Height	54 mm
Width	70 mm
Depth	113 mm
Net Weight	0.47 kg

Environment

Standards	<p>IEC 60947-4-1</p> <p>IEC 60947-5-1</p>
Product Certifications	EAC
Protective Treatment	TH conforming to IEC 60068
Ip Degree Of Protection	IP20 conforming to IEC 60529
Ambient Air Temperature For Operation	<p>-20...60 °C without derating conforming to IEC 60947-4-1</p> <p>-20...70 °C with derating</p>
Ambient Air Temperature For Storage	-60...80 °C
Fire Resistance	850 °C conforming to IEC 60068-2-1
Dielectric Strength	6 kV at 50 Hz conforming to IEC 60255-5
Electromagnetic Compatibility	Surge withstand: 6 kV conforming to IEC 60801-5

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	8.000 cm
Package 1 Width	9.000 cm
Package 1 Length	12.000 cm
Package 1 Weight	483.000 g
Unit Type Of Package 2	S02
Number Of Units In Package 2	9
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	4.690 kg

Contractual warranty

Warranty	12 months
-----------------	-----------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile [End of Life Information](#)