



PB FC RS 485 PLUG 180,
PB-PLUG WITH FASTCONNECT CONNECTOR AND
AXIAL CABLE- OUTLET F. INDUSTRY PC,
SIMATIC OP, OLM,
TRANSMISSION RATE: 12 MBIT/S,
TERMINATING RESISTOR WITH SEPARATING
FUNCTION,
PLASTIC HOUSING

Transfer rate

- with PROFIBUS

9.6 kbit/s ... 12 Mbit/s

Interfaces

Number of electrical connections

- for PROFIBUS cables
- for network components and terminal equipment

2

1

Design of the electrical connection / FastConnect

Yes

Mechanical data

material / of the housing

plastic

Design, dimensions and weight

Width

16 mm

Height

62 mm

Depth

34.5 mm

Net weight

40 g

Permitted ambient conditions

Ambient temperature

- during operating
- during storage
- during transport

0 ... 60 °C

-25 ... +80 °C

-25 ... +80 °C

Relative humidity

- at 25 °C / without condensation / during operating / maximum

75 %

Protection class IP	IP20
Product properties, functions, components / general	
Product feature / [not supplied - silicon-free]	Yes
Composant produit	
• PG connection socket	No
• décharge de traction	Yes
Standards, specifications, approvals	
Verification of suitability	
• RoHS conformity	Yes
• UL-registration	Yes
letzte Änderung:	Jul 17, 2012