

SIMATIC ET 200SP, PROFINET INTERFACE MODULE IM155-6PN BASIC, MAX. 12 PERIPHERY MODULES, 2X INTEGRATED RJ45 SOCKETS INCL. SERVERMODUL,



General information	
Product type designation	IM 155-6 PN BA with 2x RJ45 ports and server module
Firmware version	V3.2
Product function	
<ul style="list-style-type: none"> I&M data 	Yes; I&M0 to I&M3
Engineering with	
<ul style="list-style-type: none"> STEP 7 TIA Portal configurable/integrated as of version 	V13 SP1
<ul style="list-style-type: none"> STEP 7 configurable/integrated as of version 	V5.5 SP4 and higher
<ul style="list-style-type: none"> PROFINET as of GSD version/GSD revision 	V2.3 / -
Configuration control	
via dataset	Yes
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Mains buffering	

• Mains/voltage failure stored energy time	5 ms
Input current	
Current consumption, max.	300 mA
I ² t	0.09 A ² ·s
Power loss	
Power loss, typ.	1.8 W
Address area	
Address space per module	
• Address space per module, max.	32 byte; per input / output
Address space per station	
• Address space per station, max.	32 byte; per input / output
Hardware configuration	
Rack	
• Modules per rack, max.	12
Interfaces	
Number of PROFINET interfaces	1
1. Interface	
Interface types	
— Number of ports	2
— integrated switch	Yes
— RJ 45 (Ethernet)	Yes; 2 integrated RJ45 ports
— Bus adapter (PROFINET)	No
Protocols	
— PROFINET IO Device	Yes
— Media redundancy	Yes; PROFINET MRP
Interface types	
RJ 45 (Ethernet)	
• 10 Mbps	Yes; for Ethernet services
• 100 Mbps	Yes; PROFINET with 100 Mbit/s full duplex (100BASE-TX)
• Transmission procedure	PROFINET with 100 Mbit/s full duplex (100BASE-TX)
• Autonegotiation	Yes
• Autocrossing	Yes
Protocols	
Supports protocol for PROFINET IO	
• Supports protocol for PROFINET IO	Yes
PROFINET IO Device	
Services	
— Isochronous mode	No
— Open IE communication	Yes

— IRT	No
— MRP	Yes
— MRPD	No
— PROFINET system redundancy	No
— PROFlenergy	No
— Prioritized startup	No
— Shared device	No
Open IE communication	
• TCP/IP	Yes
• SNMP	Yes
• LLDP	Yes
Isochronous mode	
Isochronous operation (application synchronized up to terminal)	No
Interrupts/diagnostics/status information	
Status indicator	Yes
Alarms	
• Alarms	Yes
Diagnostic messages	
• Diagnostic functions	Yes
Diagnostics indication LED	
• RUN LED	Yes; Green LED
• ERROR LED	Yes; Red LED
• MAINT LED	Yes; yellow LED
• Monitoring of the supply voltage (PWR-LED)	Yes; green PWR LED
• Connection display LINK TX/RX	Yes; 2x green LED
Potential separation	
between backplane bus and electronics	No
between PROFINET and all other circuits	Yes
between supply and all other circuits	No
Ambient conditions	
Ambient temperature during operation	
• horizontal installation, min.	0 °C
• horizontal installation, max.	60 °C
• vertical installation, min.	0 °C
• vertical installation, max.	50 °C
Connection method	
ET-Connection	
• via BU/BA Send	No
Dimensions	

Width	35 mm
Height	117 mm
Depth	74 mm

Weights

Weight, approx.	125 g
-----------------	-------

last modified: 12.09.2015