



E32-T14LR 2M

Fiber optic sensor head, through-beam, cylindrical radial, diameter 3 mm, R1 flexible fiber, 2 m cable

Specifications

Sensing method	Through-beam
Shape	Cylindrical radial
Size	dia 3 mm
Application	Object detection
Features	Flexible fiber, Miniature
Temperature range	-40-70 °C
Sensing distance	670 mm
Cable length	2 m
Bending radius	1 mm
Free cut	✓
Material core	Plastic
Degree of protection (IP)	IP67
Sensing surface orientation	Side-view
Material sheath	Polyethylene

TERMS OF WEBSITE USE

This PDF document was created from the European OMRON Industrial Automation website on 21 June, 2024. Click here for [terms of use](#).

Related products



E3NX-CA

High-performance color mark sensor



E3NX-CA

High-performance color mark sensor



E3NX-MA

Smart Fiber Amplifier Units



E3NX-FA

High-performance digital fiber amplifier



E3X-NA

Digital fiber amplifier with potentiometer adjustment



E3X-ZV and E3X-MZV

Smart Fiber Amplifier

Downloads

CAD Library



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



Fiber Sensor Selection Selection Guide

EN PDF 16.2 MB

TERMS OF WEBSITE USE

This PDF document was created from the European OMRON Industrial Automation website on 21 June, 2024. Click here for [terms of use](#).