

# ISO cylinder DSBC-40-25-PPVA-N3

Part number: 1376656

FESTO



## Data sheet

| Feature                                  | Value  |
|--|--|
| Piston seal material                     | TPE-U(PU)  |
| Piston rod wiper seal material           | TPE-U(PU)  |
| Cushion piston material                  | POM  |
| Buffer seal material                     | TPE-U(PU)  |
| Material of piston                       | Aluminium-Knetlegierung  |
| Nut material                             | Stahl, verzinkt  |
| Flange screws material                   | Stahl verzinkt   |
| Material of bearing                      | POM  |
| Stroke                                   | 25 mm  |
| Piston diameter                          | 40 mm  |
| Piston rod thread                        | M12x1.25   |
| Type code                                | DSBC   |
| Cushioning                               | Pneumatic cushioning, adjustable at both ends                      |
| Mounting position                        | Any  |
| Conforms to standard                     | ISO 15552  |
| Piston rod end                           | External thread  |
| Design                                   | Piston<br>Piston rod<br>Profile barrel                             |
| Position sensing                         | For proximity sensor   |
| Symbol                                   | 00991235   |
| Variants                                 | Piston rod at one end  |
| Operating pressure                       | 0.6 bar ... 12 bar   |
| Mode of operation                        | Double-acting  |
| Operating medium                         | Compressed air as per ISO 8573-1:2010 [7:4:4]                      |
| Information on operating and pilot media | Operation with oil lubrication possible (required for further use) |
| Corrosion resistance class (CRC)         | 2 - Moderate corrosion stress                                      |
| Ambient temperature                      | -20 °C ... 80 °C   |
| Impact energy in the end positions       | 0.7 J  |
| Cushioning length                        | 19 mm  |
| Theoretical force at 6 bar, retracting   | 633 N  |
| Theoretical force at 6 bar, advancing    | 754 N  |
| Moving mass at 0 mm stroke               | 205 g  |
| Additional weight per 10 mm stroke       | 37 g   |
| Basic weight with 0 mm stroke            | 740 g  |
| Additional moving mass per 10 mm stroke  | 16 g   |

| Feature                     | Value   |
|-----------------------------|---|
| Type of mounting            | With internal thread<br>Optionally:<br>With accessories |
| Pneumatic connection        | G1/4  |
| Note on materials           | RoHS-compliant  |
| Cover material              | Die-cast aluminum                                       |
| Piston rod material         | High-alloy steel  |
| Material of cylinder barrel | Wrought aluminum alloy                                  |